

BORAL MATERIAL TECHNOLOGIES

Material Safety Data Sheet

This document has been prepared to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200

45 N.E. Loop 410, Suite 700
San Antonio, Texas 78216
Phone: (210) 349-4069
FAX:(210) 349-8512
E-mail: info@BORAL.com

Classification: Calcium Aluminum Silicate

Identity (as used on label and list)

Boral Celceram™ PV14A

Section I – Identity Information

Chemical Name	Emergency Telephone Number		
NA	1(800)424-9300 (CHEMTREC)		
Chemical Family	CAS#	Telephone Number for Information	
Calcium Alumina Silica Glass Spheres	68131-74-8	(210)349-4069	
Date Prepared 2/15/93	Date Revised 8/08/07		

Section II Hazardous Ingredients

Ingredients	CAS#	%Weight	%Weight	Exposure limits
			OSHA PEL	ACGIH TLV
			mg/m ³	mg/m ³
Calcium Aluminum Silicates	68131-74-8	<100%	NA	NA
Quartz (Respirable)	14808-60-7	<4%	10/(%SiO ₂ +2)	0.05
Particulates not Otherwise Regulated	NA	-	5 (R), 15 (T)	NA

The above chemistries are provided for industrial hygiene and environmental purposes and are not intended to represent product specifications. Composition is variable. This data has been compiled from data believed to be reliable. Elements such as aluminum, arsenic, boron, calcium, chromium, cobalt, copper, gold, iron, lead, molybdenum, nickel, silver, tin, titanium, vanadium, and zirconium may be present in trace amounts.

Section III – Physical/Chemical Characteristics

Boiling Point (°F)	Specific Gravity(H₂O=1)
Not Applicable	Not Applicable
Vapor Pressure (mm Hg.)	Percent Volatile by Volume(%)
Not Applicable	Not Applicable
Vapor Density (Air=1)	Evaporation Rate(Butyl Acetate=1)
Not Applicable	Not Applicable
Solubility in water	pH
Not Applicable	8-12 (1% w/w)

Appearance and Odor

Light grey powder, odorless.

Section IV – Fire and Explosion Hazard Data

Flash Point	Flammable Limits:
Not Applicable	LEL Not Applicable UEL Not Applicable

Extinguishing Media

Not Applicable

Special Fire Fighting Procedures

Not Applicable

Unusual Fire and Explosion Hazards

Not Applicable

Section V - Reactivity Data

Material as shipped is not reactive

Section VI - Health Hazard Data

ACUTE EFFECTS OF OVEREXPOSURE:

Eye: May cause irritation by abrasion with dust.

Skin: Dust may cause irritation in hypersensitive individuals.

Inhalation: Dust may cause congestion and irritation in nasal and respiratory passages.

Ingestion: No known acute effects.

CHRONIC EFFECTS OF OVEREXPOSURE:

Excessive exposures to respirable particulate (dust) over an extended period of time may result in the development of pulmonary diseases such as silicosis.

CARCINOGENICITY:

The following carcinogenicity classifications for crystalline silica have been established by the following agencies:

OSHA: Not regulated as a carcinogen

IARC: Quartz (Respirable) Group 1 carcinogenic in humans

NIOSH: Quartz (Respirable) Carcinogen, with no further categorization

NTP: Quartz (Respirable) Known Human Carcinogen

WARNING: Material may contain crystalline silica. Inhalation of dust above established or recommended exposure levels should be avoided by use of proper ventilation and/or use of a NIOSH approved respirator.

Section VII – Precautions for Safe Handling and Use

VENTILATION: Provide adequate ventilation to maintain exposures below the OSHA PEL and ACGIH TLV for quartz and other substances.

RESPIRATORY PROTECTION: None required under PEL. IF PEL is exceeded, use a NIOSH approved half or full-face air purifying respirator with high efficiency particulate air filters.

PROTECTIVE GLOVES: Work gloves as needed

EYE PROTECTION: Recommend Safety goggles or safety glasses. Eye wash stations should be readily accessible.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: As needed.

Steps to be taken in case Material is Released or Spilled: Clean up for use or disposal. Dampen with water mist to control dust (airborne dust) before removal. Do not use compressed air. If loaded on trucks wet down material to prevent dusting during transport. Observe local, state, and federal regulations pertinent to reporting requirements.

Waste Disposal Method: Dispose of in a landfill or coal ash disposal pond. Observe local, state and federal regulations. This material is not a RCRA hazardous waste.

Precautions to Be Taken in Handling and Storing: Store in dry conditions. Minimize dust. Avoid creating dust.

Section VIII – First Aid and Medical

SKIN: Wash with soap and water. If an allergic reaction causes a rash that does not heal within a few days, consult a physician

EYES: Flush with running water. Obtain medical assistance if irritation continues.

INGESTION: Do not induce vomiting. See a physician

INHALATION: Remove from exposure to airborne particulates.

Medical Conditions Aggravated by Exposure: Excessive dust exposure may aggravate any existing respiratory disorders or diseases. Possible complications or allergies resulting in irritation to skin, eyes, and respiratory tract may occur from excessive exposure to dusts.

Section IX – Other Regulations

RCRA: This material is not a RCRA hazardous waste.

EPCRA Section 311/312: Material as shipped is subject to Section 311/312 reporting due to respirable quartz content.

EPCRA Section 313: Material as shipped is not subject to Section 313, Toxic Chemical Release Inventory reporting requirements.

DOT: Material as shipped is not a hazardous material as per DOT regulations

TSCA: This material is listed in the TSCA Chemical Substance Inventory and is exempt from reporting under the Inventory Update Rule.

UN/NA Code: None

Placard Required: None

Labeling Requirement: None

The information and recommendations set forth herein are based on data we have in our possession and we have reason to believe is accurate. It is, however, the user's responsibility to determine the safety, toxicity, and suitability for his own use of the herein described product. Because the actual by others is beyond our control, Boral Materials Technologies Inc. makes no warranty expressed or implied regarding accuracy of the data or the results to be obtained from the use thereof.
